

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: C07K 5/075, A23L 1/236	A1	(11) International Publication Number: WO 00/15656 (43) International Publication Date: 23 March 2000 (23.03.00)
(21) International Application Number: PCT/NL99/00553 (22) International Filing Date: 7 September 1999 (07.09.99) (30) Priority Data: 1010063 10 September 1998 (10.09.98) NL (71) Applicant (for all designated States except US): HOLLAND SWEETENER COMPANY V.O.F. [NL/NL]; Konstraat 1, NL-6167 RA Geleen (NL). (72) Inventors and (75) Inventors/Applicants (for US only): BOESTEN, Wilhelmus, Hubertus, Joseph [NL/NL]; Brunnstroom 9, NL-6132 BJ Sittard (NL); QUADFLIEG, Peter, Jan, Leonard, Mario [NL/NL]; Kochstraat 6, NL-6164 HB Geleen (NL); SNUDER, Carina, Sascha [NL/NL]; Vogelenstraat 18, NL-6137 JR Sittard (NL); TEUNISSEN, Antonius, Jacobus, Josephus, Maria [NL/NL]; Van Ostadestraat 42, NL-6165 XM Geleen (NL). (74) Agent: DAUTZENBERG, Josef, Marie, Andreas; Octrooibu- reau DSM, P.O. Box 9, NL-6160 MA Geleen (NL).	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(54) Title: PROCESS FOR THE PREPARATION OF NEOTAME (57) Abstract <p>The invention relates to an improved process for the preparation of neotame by successively: (a) subjecting a mixture of N-benzylloxycarbonyl-L-<math>\alpha</math>-aspartyl-L-phenylalanine-1-methyl ester and 3,3-dimethylbutyraldehyde in solution to hydrogenation in a homogeneous methanolic solvent, in the presence of a hydrogenation catalyst, (b) separating the catalyst from the solution as a solid substance, (c) removing a portion, at least, of the organic part of the solvent through evaporation and optionally adding an amount of water before and/or during and/or after that evaporation and (d) separating the solid neotame formed, optionally after cooling of the system thus obtained, from the remaining liquid and drying it.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SE	Sweden
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TE	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BB	Belgium	GN	Guinea	ME	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MR	Morocco	TT	Trinidad and Tobago
BH	Bahrain	IL	Israel	MT	Malta	UA	Ukraine
BY	Belarus	IS	Ireland	MR	Mauritania	UG	Uganda
CA	Canada	IT	Italy	MW	Malawi	US	United States of America
CY	Cyprus	JP	Japan	MX	Mexico	UZ	Uzbekistan
CC	Congo	KE	Kenya	NE	Niger	VN	Viet Nam
CH	Switzerland	KG	Kyrgyzstan	NL	Netherlands	VU	Vanuatu
CI	Côte d'Ivoire	KZ	Kazakhstan	NO	Norway	ZW	Zimbabwe
CM	Cameroun	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CN	China	KR	Republic of Korea	PL	Poland		
CU	Cuba	KZ	Kazakhstan	PT	Portugal		
CZ	Czech Republic	LC	Saint Lucia	RO	Romania		
DE	Germany	LI	Liechtenstein	RU	Russian Federation		
DK	Denmark	LK	Sri Lanka	SD	Sudan		
EE	Estonia	LR	Liberia	SE	Sweden		
				SG	Singapore		

PROCESS FOR THE PREPARATION OF NEOTAME

5

The invention relates to an improved process for the preparation of neotame from an aspartame compound and 3,3-dimethylbutyraldehyde under  
10 hydrogenating conditions in a solvent.

Neotame is a recently developed, new synthetic, intensive sweetener with a sweetening power which, on a weight basis, is about 10,000x the sweetening power of sugar, and which hence also has a  
15 very high sweetening power in comparison with the sweetening powers of other intensive sweeteners so far known. Neotame is for example at least 50x as sweet as aspartame on a weight basis. The chemical structure of neotame corresponds largely to that of aspartame, it  
20 being understood that in neotame the free amino group occurring in the aspartyl part of the aspartame molecule has been substituted with a 3,3-dimethylbutyl group. Neotame can be chemically defined as *N*-(*N*-(3,3-dimethylbutyl)-*L*- $\alpha$ -aspartyl)-*L*-phenyl-alanine-1-methyl  
25 ester. Aspartame can be chemically defined as *L*- $\alpha$ -aspartyl-*L*-phenylalanine-1-methyl ester, and will also be referred to as APM below.

A process for the preparation of neotame is described in US-A-5,728,862. In that process an  
30 approximately equimolar mixture of aspartame and 3,3-dimethylbutyraldehyde is subjected to hydrogenation in an organic solvent (i.e. a solvent that contains at most 70 wt.% water; the organic solvent is preferably an alcohol, in particular methanol) and in the presence  
35 of a hydrogenation catalyst, under suitable conditions

in terms of temperature (20-30°C) and pressure, after which the catalyst is separated from the solution as a solid substance and a water/organic (ratio in the range from 70:30 to 83:17) solvent system is subsequently  
5 prepared from the organic phase, from which neotame can be separated via crystallisation.

This method is laborious and time-consuming because aspartame must first be prepared and recovered, and must subsequently be absorbed into an organic  
10 solvent for the hydrogenation step. The method consequently demands many process steps and is relatively expensive.

Aspartame is generally prepared either chemically or enzymatically. In the chemical  
15 preparation of aspartame use is often made of coupling of an N-protected L-aspartic anhydride, e.g. N-formyl-L-aspartic anhydride, and L-phenylalanine (or the methyl ester thereof). In the (more selective) enzymatic processes for the preparation of aspartame, an N-  
20 protected L-aspartic acid derivative, e.g. N-benzyloxycarbonyl-L-aspartic acid, is in practice often coupled with L-phenylalaninemethyl ester. The desired  $\alpha$ -coupling product is then formed in a selective manner. In all the processes for the preparation of  
25 aspartame the ultimate recovery of the product in a solid form (e.g. through crystallisation, solid/liquid separation and drying, etc.) is a very important part of the overall process.

In other processes for the preparation of  
30 neotame so far described the reductive amination step takes place in a solvent system that contains, inter alia, an amount of acetic acid. Such preparation processes (e.g. in US-A-5,510,508) yield a product that is not pure enough for use as a sweetener in foodstuffs

intended for human consumption. Such preparation processes moreover involve substantial deactivation of the employed catalyst, which leads to the consumption of large amounts of catalyst. Such solvent systems are  
5 also unattractive from the viewpoint of corrosion of equipment, and effects on the environment.

There is therefore a need for an improved process for the preparation of neotame which can be easily used on an industrial scale, without the  
10 aforementioned drawbacks, in which neotame can be obtained in relatively few process steps, with a favourable amount of catalyst consumption, via a simple hydrogenation step.

It has now surprisingly been found that  
15 neotame can be prepared from an aspartame compound and 3,3-dimethylbutyraldehyde under hydrogenating conditions in a highly efficient manner, in very few process steps, namely in only one process step, and without the interim isolation of aspartame, by  
20 successively

- (a) subjecting a mixture of *N*-benzyloxycarbonyl-L- $\alpha$ -aspartyl-L-phenylalanine-1-methyl ester and 3,3-dimethylbutyraldehyde in solution to hydrogenation in a homogeneous methanolic solvent, in the  
25 presence of a hydrogenation catalyst,
- (b) separating the catalyst from the solution as a solid substance,
- (c) removing a portion, at least, of the organic part of the solvent through evaporation, and optionally  
30 adding an amount of water before and/or during and/or after that evaporation, and
- (d) separating the solid neotame formed, optionally after cooling of the system thus obtained, from the remaining liquid and drying it.

In the process according to the invention *N*-benzyloxycarbonyl-L- $\alpha$ -aspartyl-L-phenylalanine-1-methyl ester (also referred to as Z-APM) is used as the aspartame compound. Wherever this application refers to *N*-benzyloxycarbonyl (or to Z) this is also understood to be any other protecting group equivalent to the Z protecting group that can be separated through hydrogenolysis, e.g. *N*-benzyloxycarbonyl groups which contain one or more substituents in their aromatic ring, such as *N*-p-methoxy-benzyl-oxy carbonyl.

A homogeneous methanolic solvent is in the context of this application understood to be both methanol and homogeneous mixtures of methanol with another solvent miscible with it or with a combination of solvents miscible with it. Such a solvent that is miscible with methanol will of course show inert behaviour under the chosen hydrogenating conditions and relative to the components present in the reaction medium. Examples of such solvents that are miscible with methanol are water, organic solvents such as lower alcohols ( $C_1$ - $C_4$ ), lower aliphatic ketones ( $C_3$ - $C_6$ ), e.g. acetone or methyl isobutyl ketone (hereinafter also to be referred to as MIBK), and ethers, e.g. diethylether, in all cases optionally also combined with an amount of water, providing that amount of water does not lead to inhomogeneity of the solvent system.

The homogeneous methanolic solvent is preferably a mixed solvent of methanol and MIBK, and optionally another solvent miscible with it, the solvent most preferably containing 20-95 wt.% methanol, more in particular 45-90 wt.%. Such mixed solvent systems are particularly advantageous because, on the one hand, there will be a homogeneous system under a wide range of hydrogenation conditions and, on the

other, solvent combinations of methanol and MIBK are commonly used, or easily obtainable by adding methanol, in enzymatic processes for the preparation of Z-APM. See for example US-A-5,693,485. In such a case Z-APM  
5 does not first have to be isolated and purified before being converted into neotame, but can be converted into neotame directly from the solution in MIBK. Advantages of such a route via Z-APM (in particular also over routes via APM) are first of all that no interim  
10 recovery (and optional purification) of APM is required. In addition, the route to neotame via Z-APM clearly involves less formation of by-products and higher yields.

The reaction according to the invention, in  
15 which Z-APM is converted into neotame, proceeds excellently in a homogeneous solution. Usually, all the components of the reaction system, except the catalyst, will be present in solution. In the case of high concentrations, one or more of the components may  
20 however crystallise somewhat during the reaction, depending on the solvent system used and the temperature of the reaction. Such crystallisation need not be disadvantageous in the process, but will demand additional measures in the upgrading steps to be able  
25 to guarantee good separation of the catalyst. The reaction system must for example be heated somewhat first, until all the precipitate formed has dissolved, or an extra amount of methanol has to be added. Such measures can easily be realised by a person skilled in  
30 the art.

In general, in the process according to the invention it will be ensured that such an amount of methanol is present during the reaction, and that the reaction temperature is such that no crystallisation of

organic product will occur before the catalyst has been separated.

The reaction mixture present during the hydrogenation reaction can be composed in any suitable manner. It is for example possible to first introduce the Z-APM, or a portion thereof, into the solvent system and dissolve it, and then add the catalyst and the 3,3-dimethylbutyraldehyde, and if necessary the rest of the solvent system. It is also possible, as already indicated above, to use product streams in MIBK that become available during enzymatic coupling processes for the preparation of Z-APM, to which methanol may optionally be added, and to subsequently add the catalyst and the 3,3-dimethylbutyraldehyde to it. This also holds when Z-APM is made available in an MIBK product stream via a chemical coupling process.

The 3,3-dimethylbutyraldehyde to be used is commercially available.

Generally, any hydrogenation catalyst known to a person skilled in the art can be used as the hydrogenation catalyst. Preferably use is made of a palladium-on-carbon catalyst. In particular, the palladium-on-carbon catalyst preferably contains 0.1 to 15 wt.% Pd, more in particular the catalyst contains 2-10 wt.% Pd, relative to the catalyst's dry weight. Suitable Pd/C-catalysts are commercially available, e.g. via Engelhard, Degussa or Johnson-Matthey.

The temperature during the hydrogenation will usually be 25-65°C. At a temperature lower than 25°C the reaction will not, or virtually not, be initiated, at a temperature higher than 65°C there will be an unnecessarily high risk of the formation of undesired by-products.

The pressure at which the hydrogenation is



carried out is usually not very critical. Preferably the hydrogenation step is carried out at atmospheric pressure, with carbon dioxide formed from the Z protecting group immediately being blown down. When the  
5 hydrogenation step is carried out at a pressure higher than atmospheric pressure it is preferable to refresh the gas cap (which will come to contain an increasing amount of carbon dioxide during the reaction) with hydrogen gas from time to time. It is less suitable to  
10 carry out the hydrogenation step at a pressure lower than atmospheric pressure.

The progress of the hydrogenation reaction can optionally be easily followed via HPLC (high-performance liquid chromatography) analyses of samples  
15 taken during the reaction. The hydrogenation step will take approx. 1 to 20 hours, depending on the catalyst chosen (type and amount) and other reaction conditions. This can easily be determined by a person skilled in the art.

20 The catalyst can be separated from the solution as a solid substance via all the standard techniques for solid/liquid separation known to a person skilled in the art, providing allowance is where necessary made for all the properties of the catalyst  
25 used known to a person skilled in the art, such as any pyrophoric properties. After the catalyst has been separated from the otherwise homogeneous reaction mixture, the neotame formed is recovered therefrom. It is preferable to first concentrate the reaction  
30 mixture. This will generally be effected through evaporation.

To minimise the formation of by-product, said evaporation will preferably take place at 25-70°C. The best results are obtained when sufficient water to

keep the products present in solution is present during the evaporation, and in particular shortly before any crystallisation could take place. That amount of water can easily be determined by a person skilled in the art. A rule of thumb is that the amount of water is so high that all the neotame formed in the reaction is still entirely soluble at the temperature of the evaporation. Extra water will therefore optionally be added during the evaporation. As already mentioned, water is added preferably while a homogeneous solution is still present, i.e. before any crystallisation of neotame occurs. It is particularly advantageous to add water if the solvent system also contains MIBK. In that case the water present also plays a part in the azeotropic and complete removal of MIBK.

Water is preferably added in an amount such that about 50 to 500 wt.% water, relative to the total original amount of organic matter, that is, the total amount of organic solvent and employed organic products, is added.

The organic solvent removed through evaporation can be used again in the process for the preparation of neotame.

The neotame crystallises as a white crystalline compound during or after the evaporation. Preferably an amount of water is added such that the neotame does not yet crystallise during the evaporation, but crystallises only after all the organic solvent has been removed; more in particular the crystallisation of neotame preferably takes place only after cooling from the temperature level during the evaporation to a (lower) temperature in the range from 40 to 0°C.

In a special embodiment of the present

invention, namely that in which the hydrogenation reaction is carried out in a mixture of methanol and MIBK (and optionally a little water), after, optionally with the addition of more water, methanol has been removed, an azeotropic mixture of water and MIBK is removed through distillation, and extra water may optionally be added in the last phases of the evaporation to remove all the MIBK. Complete removal of the organic part of the solvent is preferable.

10           After the crystallisation of neotame (and optionally further cooling of the crystallisation system) the solid neotame obtained can be separated via any technique known to a person skilled in the art, e.g. by means of filtration or centrifugation. After  
15 the separation the neotame obtained can optionally be washed, preferably with cold water, and optionally recrystallised. The neotame thus obtained, optionally washed and/or recrystallised, can be dried in any way known to a person skilled in the art. The drying  
20 temperature is however preferably not chosen to be higher than 80°C in view of the risks of decomposition and/or the formation of by-product. Drying can optionally be effected at lowered pressure.

          The invention will now be further  
25 elucidated with reference to some examples and comparative examples, without being limited in any way by the way in which the experiments have been carried out.

          The concentrations of known and unknown  
30 components in samples taken at different times, or in the end products obtained, were each time determined by means of elution high-performance liquid chromatography (HPLC). In all the HPLC determinations use was made of a column, measuring 250 x 3 mm, packed with Inertsil

ODS 5  $\mu$ m, at an oven temperature of 40°C. The following eluants were used: solvent A = 10 mM  $H_3PO_4$ , solvent B = acetonitrile. At t = 0 min. the composition was: 98% A and 2% B; at t = 35 min.: 10% A and 90% B. The run time was each time 40 minutes, at a flow rate of 1.2 ml/min. and an injected volume of 20  $\mu$ l. A photometric UV detector was used for the detection at 210 and 257 nm. All the samples were incorporated in a mixture of 50% methanol and 50% aqueous phosphate buffer, 0.05 M and pH 3.

The samples were taken and analysed in ways known to a person skilled in the art.

Example I : Preparation of neotame from Z-APM in methanol at 40°C

42.8 g of Z-APM (100 mmol) was dissolved in 500 ml of methanol in a glass 3-litre reaction vessel fitted with a hydrogen dosage device, a stirrer and a drain pipe. 1 g of 5 wt.% Pd/C (which contains 50 wt.% water) and 10 g (100 mmol) of 3,3-dimethylbutyraldehyde were added. The reactor was inertised with the aid of  $N_2$ , after which the nitrogen was replaced by 10 l of  $H_2$ /hour. The whole was heated to 40°C, after which the reaction started. After 9 hours the reaction was stopped. The catalyst was removed through filtration. The solution was concentrated through evaporation using the Rotavapor at 40°C, at lowered pressure, to approx. 100 ml, after which so much water was added that a precipitate began to form. The mixture was heated to 50°C, which led to the formation of a clear solution. The solution was subsequently cooled to 10°C, after which the neotame crystallised as a white crystalline product. The solid product was separated via filtration and washed using, successively: 30 ml of water and 4 x

50 ml of heptane. The product was subsequently dried in air at room temperature overnight. 34 grams of the product was obtained, which had a neotame content (determined via HPLC) of 87% (at least 10% of the remaining 13% being present as water). This corresponds to a yield of 78% neotame relative to the amount of Z-APM used.

10 Comparative Example A: Preparation of neotame from aspartame in MeOH at 40°C

29.4 g (100 mmol) of aspartame (APM) was dissolved in 500 ml of methanol as described in Example I 1 g of 5 wt.% Pd/C (which contains 50 % water) and 12 g (120 mmol) of 3,3-dimethylbutyraldehyde were added. The reactor was inertised with the aid of N<sub>2</sub>, after which the nitrogen was replaced by 18 l of H<sub>2</sub>/hour. The whole was heated to 40°C, after which the reaction started. After 9 hours the reaction was stopped. HPLC analysis of the solution revealed a degree of conversion of 98%. The reaction mixture was not upgraded.

Table I below shows the amounts of by-products formed in the example and the comparative example. In addition to neotame (the main product), a few known components (namely: demethylated neotame, referred to as Neo-AP; APM; the diketopiperazine of APM, referred to as DKP-APM; and residual Z-APM) and unknown components (Comp.A with a retention time of 12.7 minutes; Comp.B with a retention time of 29.1 minutes) were found to be present. The corresponding peak areas are shown in the table, and the concentrations (in wt.%) of the known compounds.

Table I

Ex. / Comp. ex.	Reaction time (hours)	Neo-AP	Comp. A ret. 12.7 min.	DKP-APM	APM	Neotams	Z-APM	Comp. B ret. 29.1 min.	water
Ex. I									
Peak area HPLC	9	213	138	76	607	12579	145	162	---
Conc. (wt.%) of isolated product		1.34	n.d.	0.2	0.56	87	<0.01	n.d.	4.9
Comp.									
Ex. A									
Peak area HPLC	8.5	28	95	61	27	12533	-	1303	---
Content in sol. (%)				0.03	0.12	8			

n.d. = not determined

Table I shows that more known by-products (e.g. Neo-AP) are produced in the reaction in which Z-APM is used as a starting material. Far more unknown by-products (in particular Comp. B) are produced in the comparative reaction, in which APM is used as a starting material.

Example XI : Preparation of neotame from Z-APM in methanol at 60°C

42.8 g of Z-APM (100 mmol) was dissolved in 500 ml of methanol as described in Example I 1 g of 5 wt.% Pd/C (contains 50% water) and 12 g (120 mmol) of 3,3-dimethylbutyraldehyde were added. The whole was heated to 60°C. The reactor was inertised with the aid of N<sub>2</sub>, after which the nitrogen was replaced by 18 l of H<sub>2</sub>/hour. The reaction was stopped after 9 hours (100% conversion according to HPLC determination). The catalyst was removed through filtration. The whole was evaporated in the wetted-wall evaporator at 40°C and slightly lowered pressure. A white powder was obtained (41 g, with a neotame content of 88 % according to HPLC analysis). The neotame yield was hence 95%, relative to the amount of Z-APM used. See Table II for data on the purity of the product recovered.

25

Comparative Example B: Preparation of neotame from APM in methanol at 60°C

29.4 g of APM (100 mmol) was dissolved in 500 ml of methanol as described in Example I 1 g of 5 wt.% Pd/C (contains 50% water) and 12 g (120 mmol) of 3,3-dimethylbutyraldehyde were added. The whole was heated to 60°C. The reactor was inertised with the aid of N<sub>2</sub>, after which the nitrogen was replaced by 18 l of H<sub>2</sub>/hour. The reaction was stopped after 9 hours (100%

conversion according to HPLC determination). The catalyst was removed through filtration. The whole was evaporated until dry in the wetted-wall evaporator. 37.4 g of white powder was isolated. The neotame yield was 75%, relative to the amount of APM used, with due allowance for the by-products that were also formed.

Table II shows the amounts of (by-)products formed in the above example (after a reaction time of 360 minutes) and in the comparative example (after a reaction time of 305 minutes), based on the peak areas in the HPLC chromatograms obtained. In addition to neotame (main product), a few known components (namely Neo-AP; APM; and DKP-APM; no residual Z-APM) and unknown components (Comp.A, Comp.B, Comp.C. and Comp.D with retention times of 12.7 minutes, 29.1 minutes, 19.1 minutes and 19.8 minutes, respectively) were found to be present. The table indicates only the relevant peak areas; no estimates of the corresponding contents are given.

20



Table II

Ex. / Comp. ex.	Neo-AP	Comp. A ret. 12.7 min.	DKP- APM	APM	Neotame	Comp. C ret. 19.1 min.	Comp. D ret. 19.8 min.	Comp. B ret. 29.1 min.	water
Ex. II									
Peak area									
HPLC	39	189	104	187	8943	9	82	595	---
Content									
(%)	0.18	n.d.	0.94	0.49	88.1	n.d.	n.d.	n.d.	0.76
Comp.									
Ex. B.									
Peak area	33	151	70	23	8097	3	272	1201	---

It can be concluded that a higher yield of neotame is obtained from Z-APM (95%) than from APM (75%) in experiments that are otherwise the same. In addition, more unknown by-products (especially Comps. B and D) are formed from APM.

Example III : Preparation of neotame from Z-APM in MIBK : MeOH = 1 : 1

42.8 g (100 mmol) of Z-APM was dissolved in 350 ml of methyl isobutyl ketone (MIBK) as described in Example I. The mixture was heated to 40°C. 350 ml of methanol, 12 g of 3,3-dimethylbutyraldehyde (120 mmol) and 6 g of a 10 wt.% Pd/C catalyst (contains 50% water) were added. The solution was sampled 2x, after 165 minutes (sample 1) and 315 minutes (sample 2). 18 l of H<sub>2</sub>/hour was passed through for 5.5 hours. The reaction was stopped. The catalyst was removed through filtration, the solution was weighed (525 g) and analysed with the aid of HPLC (see Table III for the results; the data given therein for sample 3 are the values of the solution obtained after filtration). The analytical yield (calculated) corresponds to a yield of 90% relative to the amount of Z-APM used. An amount of 34.1 g of neotame can thus be obtained after upgrading according to the methods described above.

Table III (All the results are expressed in wt.%):

Sample at time	APM	DKP-APM	Neo-AP	Neotame	Z-APM
1 165 min.	0.095	0.006	0.013	6.45	<0.01
2 315 min.	0.047	0.006	0.013	6.28	<0.01
3 315 min.	0.091	0.008	0.35	6.50	<0.01

Comparative Example C: Preparation of neotame from APM  
in MIBK: MeOH = 1: 1

29.4 g (100 mmol) of APM was added to 350 ml of MIBK in the same way as described for Example III.

5 350 ml of methanol was added and the mixture was heated to 40°C. The APM did not all dissolve. 12 g of 3,3-dimethylbutyraldehyde (120 mmol) and 6 g of a 10 wt.% Pd/C catalyst (contains 50% water) were added. 18 l of H<sub>2</sub>/hour were passed through for 5.5 hours, which

10 resulted in a clear solution. The solution was sampled 2x, after 165 minutes (sample 1) and 315 minutes (sample 2). After the reaction had stopped, the catalyst was removed through filtration; the solution was weighed (581 g) and analysed with the aid of HPLC

15 (see Table IV for the results; the data given therein for sample 3 relate to the 581 g solution). The analytical yield (calculated) corresponds to a degree of conversion of 81% relative to the amount of Z-APM used. An amount of 30.8 g of neotame could hence be

20 obtained after upgrading according to the methods described above.

Table IV (All the results are expressed in wt.%):

Sample at time	APM	DKP-APM	Neo-AP	Neotame	Z-APM
1 165 min.	0.116	0.016	0.027	5.30	<0.01
2 315 min.	0.072	0.015	0.029	5.20	<0.01
3 315 min.	0.020	0.016	0.028	5.30	<0.01

25 Table V below shows the amounts of by-products formed in the above example and comparative example as peak areas in the HPLC chromatogram.

Table V

Ex. / Comp. ex.	Reaction time (min.)	Comp.A ret. 12.7 min.	Neo- tame	Comp.C ret. 19.1 min.	Comp.D ret. 19.8 min.	Comp.B ret. 29.1 min.
Ex. III	315	79	9688	-	753	36
Comp. Ex. C	315	61	6792	-	808	34

More unknown by-products are formed relative to the amount of neotame formed in Comparative Example C (synthesis of neotame from APM) than in Example III (ratios 903/6792 versus 858/9688). The yield from Z-APM to neotame (i.e. 90%) is also higher than that from APM to neotame in the comparative example (81%).

C L A I M S

1. Process for the preparation of neotame from an  
5 aspartame compound and 3,3-dimethylbutyraldehyde  
under hydrogenating conditions in a solvent,  
characterised in that, successively,
- (a) a mixture of N-benzoyloxycarbonyl-L- $\alpha$ -  
10 aspartyl-L-phenylalanine-1-methyl ester and  
3,3-dimethylbutyraldehyde in solution is  
subjected to hydrogenation in a homogeneous  
methanolic solvent, in the presence of a  
hydrogenation catalyst,
- (b) the catalyst is separated from the solution  
15 as a solid substance,
- (c) a portion, at least, of the organic part of  
the solvent is removed through evaporation  
and an amount of water is optionally added  
before and/or during and/or after that  
20 evaporation, and
- (d) the solid neotame formed, optionally after  
cooling of the system thus obtained, is  
separated from the remaining liquid and  
dried.
- 25 2. Process according to Claim 1, characterised in  
that the homogeneous methanolic solvent is a  
mixed solvent consisting of methanol and methyl  
isobutyl ketone and optionally another solvent  
that is miscible with them.
- 30 3. Process according to Claim 1 or Claim 2,  
characterised in that the homogeneous methanolic  
solvent contains 20-95 wt.% methanol, in  
particular 45-90 wt.%.

4. Process according to any one of Claims 1-3, characterised in that *N*-benzyloxycarbonyl-L- $\alpha$ -aspartyl-L-phenylalanine-1-methyl ester is made available as a homogeneous solution, obtained in the context of a chemical or enzymatic coupling process, in a solvent system consisting of methylisobutyl ketone to which methanol has been added.
5. Process according to any one of Claims 1-4, characterised in that a palladium-on-carbon catalyst is used as the hydrogenation catalyst, in particular a catalyst containing 0.1 to 15 wt.% Pd, in particular containing 2 to 10 wt.% Pd, relative to the dry weight of the catalyst.
6. Process according to any one of Claims 1-6, characterised in that the hydrogenation is carried out at a temperature in the range from 25 to 65°C.
7. Process according to any one of Claims 1-6, characterised in that the organic part of the solvent is entirely or partially evaporated at a temperature in the range from 25 to 70°C.
8. Process according to Claim 7, characterised in that it is ensured that sufficient water to keep the products present in solution is present during the evaporation, in particular shortly before any crystallisation could occur.
9. Process according to Claim 8, characterised in that water is added in such an amount that in total about 50-500 wt.% water, relative to the original amount of organic matter, is present before the crystallisation begins.
10. Process according to Claim 7 or Claim 8, characterised in that all the organic solvent

# INTERNATIONAL SEARCH REPORT

International Application No.

PCT/NL 99/00553

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 C07K5/075 A23L1/236

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 C07K A23L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 728 862 A (PRAKASH) 17 March 1998 (1998-03-17) cited in the application the whole document	1-12
A	WO 95 30689 A (NOFRE ET TINTI) 16 November 1995 (1995-11-16) the whole document & US 5 510 508 A cited in the application	1-12
T	WO 99 20648 A (AJINOMOTO) 29 April 1999 (1999-04-29) abstract	1-12

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document not published on or after the international filing date
- "L" document which may have priority claims or which is cited to establish the publication date of another claim or other special reason (see explanation)
- "O" document relating to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance for claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is considered with one or more other cited documents, each contribution being analogous to a person skilled in the art
- "U" document member of the same patent family

Date of the written completion of the international search

15 February 2000

Date of mailing of the international search report

22/02/2000

Name and mailing address of the ISA

European Patent Office, P.O. Box 1  
NL - 6000 CA Utrecht  
Tel. (+31) 43 386 4000 Telex 31 601 400 01  
Fax (+31) 43 386 4010

Authorized officer

Masturzo, P

Form PCT/IS/Arts (current edn) (July 1999)

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Appl. No.

PCT/NL 99/00553

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5728862 A	17-03-1998	AU 6137598 A	18-08-1998
		EP 0973795 A	26-01-2000
		NO 993676 A	28-09-1999
		NO 9832767 A	30-07-1998
WO 9530689 A	16-11-1995	FR 2719690 A	10-11-1996
		AT 169636 T	15-08-1998
		AU 681523 B	28-08-1997
		AU 2528595 A	29-11-1996
		BE 180987 A	30-01-1998
		BR 9507635 A	23-09-1997
		CA 2187901 A	16-11-1995
		CH 1147817 A	16-04-1997
		CZ 9603299 A	12-02-1997
		DE 69504059 D	17-09-1998
		DE 69504059 T	25-02-1999
		EP 0769031 A	26-02-1997
		ES 2122610 T	16-12-1998
		FI 964106 A	14-10-1996
		HU 75087 A	28-04-1997
		JP 9512809 T	22-12-1997
		MD 1175 F	31-03-1999
		NO 964745 A	08-11-1996
		NZ 285777 A	24-04-1997
		PL 317053 A	03-03-1997
		SI 759031 T	31-12-1998
		SK 144996 A	07-05-1997
		US 5510508 A	23-04-1996
WO 9926648 A	29-04-1999	JP 11130794 A	18-05-1999